JC07 Rec'd PCT/PTO 0 5 MAR 2002

FORM PTO-1390 U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE ATTORNEY 'S DOCKET NUMBER (REV. 12-2001) OT-4607 TRANSMITTAL LETTER TO THE UNITED STATES U.S. APPLICATION NO (If known, see 37 CFR 1 5 DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371 INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE PRIORITY DATE CLAIMED PCT/US00/24408 6 September 2000 7 September 1999 TITLE OF INVENTION STEP FOR ESCALATOR APPLICANT(S) FOR DO/EO/US Yoshio Tsukahara, et. al. Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: 1. It is a FIRST submission of items concerning a filing under 35 U.S.C. 371. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below. The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. V A copy of the International Application as filed (35 U.S.C. 371(c)(2)) is attached hereto (required only if not communicated by the International Bureau). has been communicated by the International Bureau. is not required, as the application was filed in the United States Receiving Office (RO/US). 6. An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). is attached hereto. a. .... Ъ. has been previously submitted under 35 U.S.C. 154(d)(4). Amendments to the claims of the International Aplication under PCT Article 19 (35 U.S.C. 371(c)(3)) are attached hereto (required only if not communicated by the International Bureau). b. have been communicated by the International Bureau. have not been made; however, the time limit for making such amendments has NOT expired. c. have not been made and will not be made. LF 81 An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)). An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). An English lanugage translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). Items 11 to 20 below concern document(s) or information included:  $11.\square$ An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. V An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13.V A FIRST preliminary amendment. 14. A SECOND or SUBSEQUENT preliminary amendment. 15. A substitute specification. 16. A change of power of attorney and/or address letter. 17. A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. A second copy of the published international application under 35 U.S.C. 154(d)(4). 18. 19. A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 20. Other items or information: Return Receipt Postcard Associate Power of Attorney Express Mail Label ET246995905US

	U.S. APPLICATION NO OF know Not Yet Assigned	s. APPLICATION NO (14 known, see 17 CEP.) 51 2 INTERNATIONAL APPLICATION NO DT Yet Assigned 70 12 PCT/US00/24408						ATTORNEY'S DOCKET NUMBER OT-4607		
1		1. The following fees are submitted:					CULATIONS F	TO USE ONLY		
	BASIC NATIONAL	_								
	Neither internationa nor international sea and International Sea	al preliminary exa arch fee (37 CFR								
	International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO\$890.00									
	International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO									
	International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4)									
	International prelim and all claims satisf	inary examination ied provisions of l								
	ENTER APPROPRIATE BASIC FEE AMOUNT =						710.00			
	Surcharge of \$130.00 months from the earl		\$							
	CLAIMS	NUMBER FILE	ED	NUMBER EXTRA	RATE	\$	710.00	-		
	Total claims	9 - 20		0	x \$18.00	\$				
٤.	Independent claims	2 - 3		0	x \$84.00	\$				
	MULTIPLE DEPENI		<u> </u>		+ \$280.00	\$	280.00			
September 1	- Amuliaant alaim			ABOVE CALCUL 37 CFR 1.27. The fees in		\$				
,,,,,,,	are reduced by		\$	<del></del>						
,	SUBTOTAL =						990.00			
There is	Processing fee of \$130.00 for furnishing the English translation later than 20 30 months from the earliest claimed priority date (37 CFR 1.492(f)).					\$				
:40	. TOTAL NATIONAL FEE =									
Il to 11 Il	Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +						40.00			
H district	*			\$	1030.00					
1 11 11 11 11 11 11 11 11 11 11 11 11 1							unt to be refunded:	\$		
***							charged:	\$		
a. A check in the amount of \$ to cover the above fees is enclosed.  b. Please charge my Deposit Account No. 15-0750 in the amount of \$_1030.00 to cover the above fees.										
	_	copy of this sheet								
	<ul> <li>c.  The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 15-0750 . A duplicate copy of this sheet is enclosed.</li> <li>d.  Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.</li> </ul>									
	NOTE: Where an 1.137 (a) or (b)) mu	et, a p	petition to reviv	e (37 CFR						
1	SEND ALL CORRESPO	ONDENCE TO.			$\setminus m$	1/A 1.	MR =			
1	Sean W. O'Brien				SIGNATU	IRF				
1		ellectual Property Dept								
1	Otis Elevator Con	s Elevator Company				V. O'Brien				
	Ten Farm Springs									
	ramington, CT (						ATION NUMBER			
					REGISTRA	NOLLE	NUMBER			

FORM PTO-1390 (REV 12-2001) page 2 of 2

# 10/070712 JC10 Rec'd PCT/FTO 05 MAR 2002

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Docket: OT-4607

Yoshio Tsukahara, et al.

Date: March 4, 2002

Appln. No.: Not Yet Assigned

Group Art Unit: Not Yet Assigned

Nat'l Phase of PCT/US00/24408

Filing Date: Concurrently Herewith

Examiner: Not Yet Assigned

Title: STEP FOR ESCALATOR

Commissioner for Patents Washington, D.C. 20231

## PRELIMINARY AMENDMENT

Dear Sir:

Prior to examination, please amend the above-identified application as follows:

## IN THE CLAIMS:

Please amend claims 5 and 6, without prejudice to or disclaimer of subject matter, to read as follows:

- 5. (Amended) The escalator step according to Claim 2 or 3, wherein the height of the cleats of the non-slip surface are formed to be higher than the tread.
- 6. (Amended) The escalator step according to Claim 2 or 3, wherein the non-slip surface is fastened to a reinforcing plate which is fixed within a cleat cutout part of the step.

## **REMARKS**

The foregoing amendments are submitted to correct improper multiple-dependency. Favorable consideration is requested.

Please charge any fee for this preliminary amendment to Deposit Account No. 15-0750, Order No. OT-4607.

Respectfully submitted,

YOSHIO TSUKAHARA, ET AL.

Sean W. O'Brien

Registration No. 37,689

Otis Elevator Company Intellectual Property Department 10 Farm Springs Farmington, CT 06032 (860) 676-5760 Nat'l Phase of PCT/US00/24408 Appendix to Prelim. Amd. Version Showing Claim Amendments

- 5. (Amended) The escalator step according to Claims 2-4 2 or 3, wherein the height of the cleats of the non-slip surface are formed to be higher than the tread.
- 6. (Amended) The escalator step according to Claims 2-5 2 or 3, wherein the non-slip surface is fastened to a reinforcing plate which is fixed within a cleat cutout part of the step.

10

15

20

25



## STEP FOR ESCALATOR

.1人有种种的

Technical field of the Invention

This invention relates to an escalator step and, in particular, to a step structure that improves safety.

## Background of the Invention

A step for an escalator is comprised of a horizontal step and a riser which hangs downward from the rear edge thereof and has a curved surface. It is typical to have a non-slip function provided to the step by forming a tread made of cleats and of a toothed surface formed on the riser made of cleats, with the pitch of the riser cleats being twice that of the step tread. It has been effective to form the toothed surface of cleats, which engage with the step tread, to the riser in order to minimize the danger of articles falling between steps, and the danger of rubber shoes, etc. being dragged between steps having a smooth surface. Therefore, this has been applied in most risers of steps for escalators in recent years.

However, there are still cases of shoes being pulled between steps due to the rubber part of the shoes sliding and contacting the toothed surface of the riser. Therefore, it is desirable to improve this in order to maintain safety on an escalator. Also, the rear edge of a step formed with a tread can cause the tip of a shoe to slip and there is a danger of loss of footing.

Japanese Kokai Patent Application Number Hei 1[1989]-285581 discloses a solution of applying a surface finishing process to the surface of a riser by using a fluorine resin. Fluorine resin is expensive and causes an increase in the cost of manufacturing a step for an escalator due to the process for coating the fluorine resin. There were additional problems. however, such as lack of durability due to the fluorine resin tending to wear out easily. The work of disassembling the entire escalator and removing steps to be repaired become necessary in order to repaint worn fluorine resin. This results in a lack of availability of the escalator during this time and an associated increase in maintenance cost.

10

15

20

Summary of the Invention

This invention was achieved by considering the aforementioned situation and improves the step for an escalator by providing a non-slip function to the rear edge of the step, along with improving the riser in order to minimize the risk of drag-in between steps.

In order to solve the aforementioned problems, this invention provides a step for an escalator having a toothed surface made of cleats and a riser which hangs downward with a curved surface from the rear edge of a horizontal step, with one or more grooves formed in the longitudinal direction of the riser cleats.

Therefore, the smooth surface of a riser cleat is eliminated due to grooves being provided to each cleat forming the toothed surface of the riser, and the danger of dragging in of rubber shoes can be minimized or prevented.

Also, a step for an escalator is provided with a riser having a curved surface which hangs downward from the rear edge of a horizontal step, and a non-slip surface of a prescribed width and a fixed length mounted detachably at the rear edge of the step.

Therefore, danger of shoes slipping inadvertently can be prevented since a non-slip function is provided to the rear edge of the step.

In a particular embodiment, the non-slip surface is composed of a synthetic resin body of a fixed length and approximately the same width as a prescribed demarcation width to be applied at the periphery of the step and is a material of greater frictional resistance than metal. Also, a serrated irregular part is formed on the top surface of the cleats of the non-slip surface. Furthermore, the height of the cleats of the non-slip surface is formed to be higher than the tread. Furthermore, the non-slip surface can be fastened with screws to a reinforcing plate, which is fixed within the cleat cutout part of the step.

10

15

20

25

## Brief Description of the Drawings

Figure 1 is a perspective view of the step for an escalator related to this invention.

Figure 2 is an enlarged view within circle A in Figure 1.

Figure 3(A) is a partially sectioned perspective view of the riser shown in Figure 1 and (B) is a partial top view thereof.

Figure 4(A) is a partially sectioned perspective view in another example of the riser shown in Figure 1 and (B) is a partial top view thereof.

Figure 5(A) is a partially sectioned perspective view in yet another example of the riser shown in Figure 1 and (B) is a partial top view thereof.

Figure 6(A) is a partially sectioned perspective view in yet another example of the riser shown in Figure 1 and (B) is a partial top view thereof.

Figure 7 is a disassembled perspective view of a non-slip member.

Figure 8 is a schematic perspective view for an assembling example of a non-slip member.

Figure 9 is a schematic perspective view for another assembling example of a non-slip member.

## Best Mode for Carrying Out the Invention

Below. embodiments of this invention will be explained by referring to the appended figures. Escalator step (1) shown in Figure 1 and Figure 2 has step (2) which maintains a horizontal surface and riser (3) which hangs downward in a curved shape from the rear edge of step (2), tread (4) comprised of plural cleats (4a) is formed on the top surface of step (2) along with toothed surface (5) composed of plural cleats (5a) having a pitch twice that of tread (4) being formed to the surface of riser (3). Along with grooves (6) being formed on each cleat (5a) which forms toothed surface (5), non-slip surface (7) is mounted to be detachable at the rear edge of escalator step (1) at which tread (4) and toothed surface (5) meet.

Grooves (6) are 2-3 grooves which are formed in the longitudinal direction on the surface of each cleat (5a) comprising toothed surface (5) as shown in Figure 3-Figure 6. The

10

15

20

25

examples shown in Figure 3 and Figure 4 show cases when riser (3) is composed of a thick plate of die cast aluminum, etc. and the examples in Figure 5 and Figure 6 shows cases when riser (3) is composed of a thin stainless steel plate, etc. With regard to grooves (6), two are formed parallel along cleat (5a) in Figure 3 and Figure 5 or three are formed parallel along cleat (5a) in Figure 4 and Figure 6. The preferred dimensions for each part shown in Figure 3(B)-Figure 6(B) are noted in detail in the item of the application example.

Grooves (6) are formed simultaneous with the die casting or pressing. Or, naturally, it is possible to form grooves (6) to cleat (5a) by machining after the formation of riser (3) by die casting. Also, the number of strip grooves (6) in each cleat (5a) is not restricted to that shown in the figures. Namely, all that is necessary is to make the area of the surface that the rubber shoes contacts in addition to the two die surfaces of each strip bump (5a) as small as possible and not to deform the rubber portion of the shoe when contact is made.

Also, non-slip surface (7) is a synthetic resin molded body which is a material having a greater frictional resistance than metal and has fixed length (L) and approximately the same width (W) as the demarcation width, with the exception of one portion (2-3 cleat bumps (4a)) of tread (4) applied with marking consisting of a yellow indicator for indicating the lateral boundary of the step at the periphery of step (2) as shown in Figure 7. Therefore, if the synthetic resin molded body is formed with a yellow material, it can replace a demarcation at the rear edge of the step.

Along with alternately forming cleats (7a) of slightly higher height and the same pitch interval as tread (4) and cleats (7b) of the same pitch interval as cleats (5a) and adjacent to cleats (7a) to this synthetic resin molded body, serrated irregular part (7c) is formed to the top surface of strip bumps (7a) and (7b) as indicated within the circle in the figure. Cleats (7a) and (7b) can be formed to be slightly higher than cleats (4a) so that the tips of shoes become caught.

In order to mount this non-slip surface (7) to escalator step (1), screw holes (8. 8) are perforated between cleats (7a) and (7b) at the top surface of non-slip surface (7) and cleat cutout part (11) is formed to the rear edge of step (2). It is preferably, if possible, to provide

10

15

20

25

WO 01/17888 PCT/US00/24408

screw holes (12a, 12a), which conform with the screw holes of non-slip member (7) to cleat cutout part (11).

If not possible, reinforcing plate (12) is provided to cleat cutout part (11) as shown in simplified Figures 8(A) and (B). This reinforcing plate (12) is formed by horizontal part (12b) with screw holes (12a) and (12a) which conform with screw holes (8) and (8) perforated in non-slip surface (7) at the end part of curved surface part (12c). The plate (12) is suitably fixed so that curved surface part (12c) contacts the inside surface of riser (3), and the top surface of horizontal part (12b) is maintained at approximately the same height as the top end surface on the riser (3) of cleat cutout part (11). Therefore, joining to reinforcing plate (12) is done by fitting non-slip surface (7) into cleat cutout part (11) and engaging fasteners (13) and (13) into screw holes (8) and (8).

Alternatively, as shown in similarly simplified Figures 9(A) and (B). slanted reinforcing plate (14) which links the inside surfaces of riser (3) and step (2) is coupled to the inside part of cleat cutout part (11) by welding, etc. Contact surface (9) is formed by cutting a bottom angular part on the step (2) side of non-slip surface (7) so as to be parallel to the slanted angle of reinforcing plate (14). Screw holes (8) and (8) are perforated at a slant so as to be orthogonal to reinforcing plate (14) fasteners (13) are engaged into screw holes (8) and (8) at a slant, and non-slip surface (7) and reinforcing plate (14) are joined.

Other alternatives include forming an extension on the non-slip surface 7. Instead of using fasteners at the bottom part of non-slip surface (7), the extension can be inserted into hole (12a) and fixed by fastening with a ring, etc. on the back side of step (2). Another alternative includes an extension that expands after press fitting and inserting it into hole (12a). In these cases, there is a disadvantage of needing to disassemble the entire escalator during maintenance such as when replacing non-slip surface (7), as opposed to the configuration using screw fastening, in which maintenance such as replacement of the non-slip surface is possible without disassembling the entire escalator.

Non-slip member (7) can be conformed in length by fabricating a fixed, prescribed length member, fixing this to cleat cutout part (11) as an extension, and suitably cutting if the length thereof [of cleat cutout part] is insufficient.

10

15

20

25

Suggested dimensions in Figure 3(B), Figure 4(B), Figure 5(B), and Figure 6(B) are about (a) 6.00 mm, (b) 1.00 mm, (c) 1.50 mm, (d) 2.50 mm, (e) 6.00 mm, (f) 7.00 mm, (g) 1.00 mm, (h) 3.00 mm, and (i) 0.3 mm. Also, if groove (6) has two grooves, the curvature radius at the awl part of the waveform in strip bump (5a) is 0.05 mm and if groove (6) has three grooves, the curvature radius of the awl part of the waveform in strip bump (5a) is 0.03 mm.

According to this invention as explained above, one or more grooves are provided to the surface of each cleat forming the toothed surface of the riser so that even if rubber shoes, etc. contact the cleat, the grooves do not cause adhesion by creating a pneumatic layer, and thus the danger of dragging in shoes, etc. between steps is minimized or eliminated, and a significant decrease in maintenance cost results compared to repainting the step with fluorine resin. Furthermore, a non-slip surface is provided to the rear edge of the step so that danger of shoes slipping at the rear edge of the step can be prevented.

Also, the non-slip surface is formed with a synthetic resin plate of a fixed length and the same width as a prescribed demarcation width, so naturally, in addition to being able to be manufactured inexpensively with a synthetic resin and functioning also as a demarcation, an effective non-slip function is manifested due to the synthetic resin material having greater frictional resistance than a metal.

Also, the cleat in the non-slip member is made slightly higher than the height of the tread so that shoe tips may be engaged. Also, an irregular part is formed at the top surface to create a more effective non-slip function.

Furthermore, the non-slip surface is configured to be attachable and detachable to the cleat cutout part of the step, so if one portion of the non-slip member breaks off, this part can be replaced immediately and a great decrease in maintenance cost can be made compared to replacing the entire step.

10

15

## What is Claimed:

1. An escalator step including a tread and a riser, the riser extending downward from a rear edge of the step, the riser including a toothed surface made of cleats with one or more grooves formed in the longitudinal direction on the surface of each of the cleats.

- 2. An escalator step including a tread and a riser, the riser extending downward from a rear edge of the step, the step including a non-slip surface of a fixed length and a prescribed width mounted to the rear edge of the step.
- 3. An escalator step according to Claim 2, wherein the non-slip surface is comprised of a synthetic resin body of a fixed length and approximately the same width as a prescribed demarcation width to be applied at the periphery of the step and is formed with cleats conforming to the step tread.
- 4. The escalator step according to Claim 2 or 3, further including a serrated irregular part formed on the top surface of the cleats of the non-slip surface.
- 5. The escalator step according to Claims 2-4, wherein the height of the cleats of the non-slip surface are formed to be higher than the tread.
  - 6. The escalator step according to Claims 2-5, wherein the non-slip surface is fastened to a reinforcing plate which is fixed within a cleat cutout part of the step.

# WO 01/17888 A

# (19) World Intellectual Property Organization International Bureau



## 

# (43) International Publication Date 15 March 2001 (15.03.2001)

## PCT

# (10) International Publication Number WO 01/17888 A1

(51) International Patent Classification<sup>7</sup>:

B66B 23/12

- (21) International Application Number: PCT/US00/24408
- (22) International Filing Date:

6 September 2000 (06.09.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 11/252446

7 September 1999 (07.09.1999) JP

(71) Applicant (for all designated States except US): OTIS ELEVATOR COMPANY [US/US]; Intellectual Property Dept., 10 Farm Springs, Farmington, CT 06032-2568 (US).


- (72) Inventors; and
- (75) Inventors/Applicants (for US only): TSUKAHARA, Yoshio [JP/JP]; 13-8, Hiyoshikura, Tomisato-Machi, Imba-Gun, Chiba 286-0202 (JP). MOTOMURA, Kazuhiko [JP/JP]; Ho-294-10, Yohkaichiba-Shi, Chiba 289-2100 (JP). TANAKA, Takashi [JP/JP]; 13-8, Hiyoshikura, Tomisato-Machi, Imba-Gun, Chiba 286-0202 (JP). MAEDA, Koichi [JP/JP]; 3-39-21, Asagayaminami, Suginami-Ku, Tokyo 166-0004 (JP).
- (74) Agents: HENLEY, Randy, G. et al.; Otis Elevator Company, Intellectual Property Dept., 10 Farm Springs, Farmington, CT 06032-2568 (US).
- (81) Designated States (national): DE, KR, US.

### Published:

With international search report.

[Continued on next page]


(54) Title: STEP FOR ESCALATOR




(57) Abstract: An escalator step riser is improved by adding grooves to the cleat surfaces, and, at the same time, a skid-inhibiting function is realized at the rear edge of the step. For escalator step (1), cleats (5a) are formed with a pitch twice that of tread (4) on riser (3). On each cleat (5a) of the riser (3), one or more grooves (6) are formed in the longitudinal direction. In addition, skid-inhibiting surface (7), made of a synthetic resin and having a prescribed width, is attached in a quick connecting/disconnecting manner on the rear edge of step (2). A serrated irregular portion (7c) is formed on the upper surface of cleats (7a), (7b) of the non-slip surface (7).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.


PCT/US00/24408





SUBSTITUTE SHEET (RULE 26)

FIG.3A









FIG.4A








SUBSTITUTE SHEET (RULE 26)












SUBSTITUTE SHEET (RULE 26)

4/5



PCT/US00/24408

5/5

FIG.8A






FIG.9A








FIG.9B

# COMBINED DECLARATION AND POWER OF ATTORNEY IN ORIGINAL APPLICATION

DOCKET NO. OT- 4607

I declare: that my residence and citizenship is as stated below next to my name; that I believe I am the original, first and sole inventor (if only I am named below) or joint inventor (if plural inventors are named below) of the subject matter for which priority is claimed under a patent application filed in Japan under Application No. 11-252446 dated September 7, 1999 and identified as Attorney Docket No. OT-4607, and for which a patent is sought in the specification entitled

## STEP FOR ESCALATOR

That I have reviewed and understand the contents of the above-identified specification, including the claims; that I acknowledge the duty to disclose to the Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. §1.56; that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

I appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Robert P. Hayter (Reg. No. <u>28,424</u>); Troxell K. Snyder (Reg. No. <u>30,804</u>); Randy G. Henley (Reg. No. <u>35,188</u>); and Thomas H. Osborn (Reg. <u>40,752</u>)

Direct all correspondence to:

Telephone:

Randy G. Henley

(860) 676-5742

Otis Elevator Company

Intellectual Property Department

Ten Farm Springs

Farmington, CT 06032

Taimington, CT 00032					
FULL NAME OF 1ST JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE			
Yoshio Tsukahara	YOSHIO TSUKAHARA	Sep 5,2000			
RESIDENCE AND POST OFFICE ADDRESS	CITIZENSHIP				
13-8 Hiyoshikura, Tomisato-Machi, Imba-Gun, Chi	Japan				
FULL NAME OF 2ND JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE .			
Kazuhiko Motomura	Kagopiko Motomura	Sep. 5.2000			
RESIDENCE AND POST OFFICE ADDRESS		CITIZENSHIP			
Ho-294-10, Yohkaichiba-Shi, Chiba Prefecture Japa	-294-10, Yohkaichiba-Shi, Chiba Prefecture Japan 289-2100				
FULL NAME OF 3RD JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE			
Takashi Tanaka	Jakashi Janaka	Sep 4, 2000			
RESIDENCE AND POST OFFICE ADDRESS 13-8, Hiyoshikura, Tomisato-Machi, Imba-Gun, Ch	CITIZENSHIP Japan				





FULL NAME OF 4 <sup>TH</sup> JOINT INVENTOR	INVENTOR'S SIGNATURE Koichi Maeda	DATE Sep. 4. 2000
RESIDENCE AND POST OFFICE ADDRESS 3-39-21 Asagayaminami, Suginami-Ku, Tokyo-to Ja	CITIZENSHIP Japan	